Indo-US Conference, New Delhi 17-18th April 2002

Coal Bed Methane and Gas Hydrate Development Programme in India

By
Dr. Avinash Chandra
Director General
Directorate General of Hydrocarbons







Coal Bed Methane Prospects and Development

in


India







Natural Gas Demand Supply Projections



- Supply projections on present reserves of conventional gas
- → 30% increase due to recent discoveries in Pvt./J.V. Sector




GROWING NEED OF COAL BED METHANE EXPLOITATION IN INDIA

- CBM AN ENVIRONMENT FRIENDLY CLEAN FUEL
- ENERGY BENEFIT OF WASTE MATERIAL
- REDUCTION OF EMISSION OF GREENHOUSE GAS
- DEGASSIFICATION REDUCES MINING RISKS
- ◆ CBM USE IN POWER STATIONS AND OTHER INDUSTRIES




CHRONOLOGY OF CBM DEVELOPMENT IN INDIA






COAL AND LIGNITE FIELDS OF INDIA





PERMEABILITY OF SOME TESTED GONDWANA COAL SEAMS SHOWN ON PERMEABILITY VERSUS DEPTH PLOT OF COAL BEDS OF USA





VISUALISED PRODUCTION CHARACTERISTICS OF INDIAN COAL BED METHANE RESERVOIRS

- ♦ Heterogeneous Indian coal a complex reservoir
- Permeability moderate
- ◆ Low permeability compensated by large thickness (k x h)
- Coal under subhydrostatic pressure upto 300m depth.
- ◆ Jharia test well yields 8000 m³/d of gas flow
- Water production low
- ◆ Blocks hold promise of 2-3 MMSCMD gas production



CBM BLOCK IN HIGH RANK COALZONE IN JHARIA COALFIELD







JHARIA COALFIELD – A STOREHOUSE OF COALBED METHANE

♦ COAL SEAMS : 18 Regional Seams

◆ THICKNESS : 1 – 33 m

◆ DEPTH : 300 – 1200 m

◆ GAS CONTENT : Usually 6 – 16 m³/t

◆ PERMEABILITY : 0.03 (Deeper Seam) to 3.0 md (Upper Seam)


◆ GAS PRODUCTION : 8000 m3/d or 300,000 ft3/d in test well

◆ WATER PRODUCTION : 2 – 5 m3/d

R&D ACTIVITY : UNDP Project in another part of this field




GEOLOGICAL MAP OF RANIGANJ COALFIELD SHOWING OFFERED CBM BLOCKS





STATUS OF CBM EXPLORATION IN INDIA

ADSORPTION ISOTHERM TEST OF COAL SEAMS IN SOUTH WESTERN PART OF RANIGANJ COALFIELD





RANIGANJ COALFIELD IN THRESHOLD OF CBM DEVELOPMENT

◆ THREE CBM BLOCKS : East Raniganj (500 Sq.Km.)

North Raniganj (350 Sq.Km.)

South Raniganj (210 Sq.Km.)

◆ SEAM THICKNESS : 4 – 46 m

♦ GAS CONTENT : 2 – 17 m³/t


PERMEABILITY : Good upto 800m depth

◆ ANTCIPATED GAS : 2 – 3 MMSCMD

PRODUCTION



GEOLOGICAL MAP OF BOKARO COALFIELD





BOKARO COALFIELD: A SMALL YET AN EXCELLENT CBM PROSPECT

◆ COAL SEAMS : 22 Nos.

◆ THICKNESS OF SEAMS : 2 – 36 m

◆ DEPTH : 300 – 1500 m

◆ GAS CONTENT : 6 – 12 m³/t

HYDROGEOLOGY : Sub artesian at places

◆ PERMEABILITY : Continuous gas emission from


old boreholes shows good

permeability

◆ ANTICIPATED PRODUCTION : 2 MMSCMD




GEOLOGICAL MAP OF SOHAGPUR COALFIELD





PROSPECTIVE CBM BLOCK IN SONHAT COALFIELD, CHHATTISGARH





SOHAGPUR – SONHAT COALFIELDS A CBM SOURCE IN LOCALLY FORMED HIGH RANK COALS

Local development of high rank coal in regional low rank coal domain

◆ Coal Seam : 5 – 6 Nos.

♦ Thickness : 1 – 12 m


◆ Gas content : 3 – 10 m3/t

Production prospect : Good as large command

area available for CBM exploitation



SCHEMATIC MAP OF PROPOSED CBM BLOCKS, CAMBAY BASIN




- 1. ALLUVIUM
- 2. NEOGENE
- 3. PALAEOGENE
- I. DECCAN TRAP
- 5. UPPER CRETACEOUS
- 6. LOWER CRETACEOUS
- 7. ERINPURA GRANITE
- 8. DELHI SUPER GROUP
- 9. ARAVALI SUPER GROUP
- 10. ARCHAEN
- 11. PRECAMBRIAN TREND
- 12. PLAEOGENERIFT MARGIN
- 13. NEOGENE MARGIN
- 14. PREMORDIAL FAULTS
- 15. MAJOR TRANSFER FAULTS
- 16. COAST LINE



DGH

SECTION SHOWING DEVELOPMENT OF THICK LIGNITE SEAMS IN SOBHASAN AREA, CAMBAY BASIN, GUJARAT





CBM PROSPECT IN CAMBAY BASIN, GUJARAT

BLOCK AREA

: 2220 Sq.Km.

LIGNITE THICKNESS

: 10 - 23 m

DEPTH

: 900 – 1400 m

GAS CONTENT


: 3 - 5 m3/t

PERMEABILITY

: 1 - 3 md



GEOLOGICAL MAP OF BARMER BASIN






LITHOLOGICAL SEQUENCE INTERSECTED IN GUDA-1 WELL

AGE	FORMATION	LITHOLOGY	DEPTH (M)
RECENT	Alluvium Grave	162m 385m 650m 852m 1079m	
MIOCENE- PLIOCENE	KALIANA Grave		
	JAGADIA		
	KAND		
	BABAGURU Cha		
Oligo	WAV	Mari, Shale & Lignite	1105m
100.700	UPP. THARAD	Sandy shale & Silt unconfirmity	1319m
4 4 4	With the Property of	Lignite, Silty Clays	1374m 1817m
MIDDLE	MID. THARAD	Shales, sandy & silty at top, Lignite & Carb. Shale.	
	LR. THARAD	Lignite, Clay & Silty Sands	



ADSORPTION ISOTHREM OF LIGNITE SEAMS, GUDA WELL-1, BARMER BASIN, RAJASTHAN





CBM PROSPECT IN BARMER BASIN, RAJASTHAN

North Block offered earlier

South Block

Area : 1111 Sq. Km.

• Lignite : 40 - 60 m


• Depth : 500 - 1500 m

• Gas Content : 3- 5 m³/t. Adsorption isotherm

: 7.2 m3/t at 41.5 kg/Cm2




LOCATION MAP OF LIGNITE FIELDS IN TAMILNADU





ADSORPTION ISOTHERM OF MANNARGUDI LIGNITE FROM BOREHOLE AT 472.3 m DEPTH





MANNARGUDI LIGNITE BASIN, TAMILNADU – A FUTURE CBM PROSPECT

◆ TOTAL PROSPECTIVE AREA : 500 Sq. Km.

◆ LIGNITE THICKNESS : 10-90 m

◆ LIGNITE DEPTH : 200-500 m

◆ LIGNITE RESERVES : 20 Billion Tonnes

GAS CONTENT

• SORPTION CAPACITY (MAX.) : 3.9-4.3 m³/t

• DESORPTION TEST : 0.87 m³/t

ANALOGY WITH POWDER RIVER BASIN



WORK PROGRAMME IN 5 OFFERED CBM BLOCKS AND PRODUCTION POSSIBILITY

S.No.	CBM Block	Duration of Exploration Phase	No. of Wells to be drilled	Estimated Expenditure In Crores	DGH Projection of Peak Production in Exploitation Stage in MMSCMD
1	RANIGANJ EAST RG(EAST)-CBM-2001/1	Phase I – 2 years Phase-II – 3 years	87	21.02	1.5
2	BOKARO BK-CBM-2001/1	Phase I – 2 years Phase II – 4 years	20	14.58	1.9
3	NORTH KARANPURA NK-CBM-2001/1	Phase I – 2.5 years Phase II – 4 years	15	7.97	2.0
4	SOHAGPUR (EAST) SP(EAST)-CBM-2001/1	Phase I – 2 years Phase II – 1.5 years	18	6.20	1.8
5	SOHAGPUR (WEST) SP(WEST)-CBM-2001/1	Phase I – 2 years Phase II – 1.5 years	18	6.24	1.8
					9.0

Thank you